

Power Clean

Overview

Concentrated, high performance, alkaline cleaner designed for use on workshop, depot and garage floors, and inspection pits. Quick action and low foam makes it ideal for use in scrubber drying and rotary machines

Technical description

A complex and highly concentrated formulation comprising high performance bio-based cleaning agents to compliment traditional chemistries, together with complexing and anti-deposition agents to ensure deposits are easily rinses away. Low foaming properties make this an ideal product for manual and machine application where foam generation is problematic and a stable emulsion is to be avoided.

For applications on porous surfaces where biodegradation of oils and greases is desired, use Waterman Biocare Technologies OilOff as an alternative to Power Clean

Features	Benefits
Aqueous, water-dilutable formulation	Fast Acting. Shortens clean-up time
Contains no petroleum distillates or solvents	Versatile: Can be used as a manual and machine cleaner
Non-corrosive to skin	Low cost in use
All ingredients are highly biodegradable	Leaves surfaces clean, streak-free and shiny
Improved rinsing performance	Removes oil and grease, ordinary soil and grime
Effective at low temperature	
Easy application and removal	
Effective in both hard and soft water areas	

The information provided in this Technical Data Sheet is accurate at the date of issue and should be used for indicative purposes only. Please refer to your Company Representative for specific User instructions as to how these relate to your usage requirements. Please note that Waterman Biocare Technologies Ltd is not liable for claims, damages, costs or expenses of any kind arising from the mishandling of the product or changes that might occur during the handling, storage and application conditions provided by any third party who does not follow the minimum requirements defined in the SDS. Please refer to the SDS for further information regarding the handling, storage and application procedures for the product.

Waterman Biocare Technologies Ltd. Aqua House, Europa Way, Britannia Enterprise Park, Lichfield, Staffordshire, WS14 9TZ, United Kingdom.

Applications / Directions for use

Where deposits have accumulated over time, first remove as much debris and solid material as possible.

Dilution rate:

Heavy soil 1 to 10 (10%)

Medium soil 1 to 25 (4%)

Light soil 1 to 50 (2%)

Packaging

2x5 L case

20 L jerry cans

200L drum

1000L IBC

The information provided in this Technical Data Sheet is accurate at the date of issue and should be used for indicative purposes only. Please refer to your Company Representative for specific User instructions as to how these relate to your usage requirements. Please note that Waterman Biocare Technologies Ltd is not liable for claims, damages, costs or expenses of any kind arising from the mishandling of the product or changes that might occur during the handling, storage and application conditions provided by any third party who does not follow the minimum requirements defined in the SDS. Please refer to the SDS for further information regarding the handling, storage and application procedures for the product.

Waterman Biocare Technologies Ltd. Aqua House, Europa Way, Britannia Enterprise Park, Lichfield, Staffordshire, WS14 9TZ, United Kingdom.